



- Pannello superiore in acciaio inox
- Stainless steel top panel
- Panneau supérieur en acier inox
- Edelstahl oben Teil
- Panel superior en acero inox

- Pannello inferiore in acciaio inox
- Stainless steel bottom panel
- Panneau socle en acier inox
- Edelstahl unter Teil
- Panel inferior en acero inox

- 800 ÷ 1000
- 1x230 V
50 Hz
- 350x350 mm



- Dosatore Detersivo Peristaltico regolabile
- Adjustable Peristaltic Soap Pump
- Doseur de produit de lavage
- Spülmitteldosierer, regulierbar
- Dosificador de detergente regulable



- Pompa di scarico
- Drain pump
- Pompe de vidange
- Ablaufpumpe
- Bomba de desagüe

CARATTERISTICHE TECNICHE - TECHNICAL DATA - CARACTERISTIQUES TECHNIQUES - TECHNISCHE EIGENSCHAFTEN - CARACTERÍSTICAS TÉCNICAS

Alimentazione elettrica Electric supply <i>Alimentation électrique</i> Betriebsspannung <i>Alimentación eléctrica</i>	1x230 V/50Hz	Capacità vasca Wash tank capacity <i>Capacité cuve</i> Wanneninhalte <i>Capacidad cuba</i>	lt. 11	Pressione alimentazione Required water pressure Pression alimentation Wasserzulaufdruck Presión alimentación	bar 2 ÷ 4
Potenza pompa lavaggio Wash pump power <i>Puissance pompe de lavage</i> Pumpenleistung <i>Potencia bomba lavado</i>	Kw 0,22 (HP 0,30)	Capacità boiler Boiler capacity <i>Capacité surchauffeur</i> Boilerinhalt <i>Capacidad boiler</i>	lt. 5	Ø tubo di carico/scarico Water supply hose/drain hose Diamètre tuyau d'entrée/de vidange Einfüllschlauch/Abflussschlauch Ø tubo de carga/de desagüe	3/4" / 25
Resistenza boiler Boiler element <i>Puissance résistance surchauffeur</i> Heizleistung Boiler <i>Potencia resistencia boiler</i>	W 2700	Temperatura lavaggio/risciacquo Wash-rinse temperature <i>Température lavage-rinçage</i> Spül-Nachspültemperatur <i>Temperatura lavado-aclarado</i>	55° / 85°	Acqua alimentazione Supply water Eau d'alimentation Anschlussstemp Agua de alimentación	Max 50°C
Resistenza vasca Tank element <i>Puissance résistance cuve</i> Heizleistung Wanne <i>Potencia resistencia cuba</i>	W 1800	Durata ciclo Cycle time <i>Durée du cycle</i> Spülzyklusdauer <i>Duración ciclo</i>	120 sec.	Livello rumorosità Noise emission <i>Émission sonore</i> Arbeitsplatzbezogener emissionswert <i>Emisión de ruidos</i>	< 60 dBA
Potenza massima assorbita Total power rating <i>Puissance maximale</i> Max Stromaufnahme <i>Potencia máxima</i>	W 2920	Cicli ora Cycles/hour up to Cycles par heure Körbe pro Stunde Ciclos/h	30	Peso netto Net Weight <i>Poids net</i> Netto Gewicht Peso neto	Kg 27